TIMER INSTRUCTION MANUAL
TEMPLATE DESIGN GUIDE

ALL INSTRUCTION MANUALS AND RELATED MATERIAL CREATED THROUGH ADAPTATION OF THESE TEMPLATES MUST BE APPROVED BY LOWE'S PRIVATE BRAND CREATIVE SERVICES DEPARTMENT PRIOR TO PRODUCTION.
CONTACT:
LOWE'S BRAND EXCHANGE (LBX)
LOWESBRANDEXCHANGE@LOWES.COM

ARTWORK DISCLAIMERS

ALL GRAPHICS SHOWN ARE FOR SIZE AND POSITION ONLY; FINAL LINE-ART GRAPHICS ARE REQUIRED FOR RELEASE TO PRESS.

IMPORTANT VENDOR NOTE

VENDORS ARE RESPONSIBLE FOR THE EXECUTION AND ACCURACY OF THEIR INSTRUCTION MANUALS. THEY ARE SOLELY RESPONSIBLE FOR INSERTING ALL OF THE CORRECT LEGAL CERTIFICATION, WARNING, WARRANTY, AND OTHER APPLICABLE PRODUCT INFORMATION. LOWE'S IS NOT RESPONSIBLE FOR ANY INCURRED DESIGN, TRANSLATION OR PRINTING COSTS. PLEASE REFER TO THE TRANSLATION REQUIREMENTS ON LOWESLINK.COM

LOWE'S REQUIRES EACH VENDOR TO OBTAIN THEIR OWN LINE-ART GRAPHICS.

COLOR USAGE & PRINT REQUIREMENTS

DO NOT USE ANY COLOR GRAPHICS OR PHOTOGRAPHY IN YOUR INSTRUCTION MANUALS. INSTRUCTION MANUALS PRINT IN GREYSCALE ONLY.

100% BLACK

REQUIRED PAPER TYPE
USE THE FOLLOWING PAPER FOR YOUR INSTRUCTION MANUALS:
- PAPER BASIS WEIGHT: 20-lb. PAPER OR 75 GRAMS/SQ METER
- DOCUMENT SIZE: PRINTED TWO-SIDES ON LETTER SIZE PAPER – TWO-FOLD DESIGN. FOLD TO FIT PACKAGE

Editable Text (DO NOT PRINT) — THIS COLOR INDICATES ALL TEXT TO BE CHANGED WITH PRODUCT SPECIFIC TEXT.

CALLOUTS (DO NOT PRINT) — THIS COLOR IS USED FOR NOTES AND DOES NOT PRINT.

FONT & SOFTWARE USAGE STATEMENT

- FONTS USED ON THIS FILE: SEE FONT LEGEND
- CONTACT YOUR APPROPRIATE FONT VENDOR TO PURCHASE THE REQUIRED FONTS FOR THIS PACKAGE LINE
- ADOBE INDESIGN CS5 WAS USED TO CREATE THIS FILE

FONT LEGEND

ALL FONTS MUST BE ARIAL BOLD OR ARIAL REGULAR, 10 PT. (MINIMUM) ON 12 PT. LEADING UNLESS OTHERWISE SPECIFIED.

THIS DESIGN IS PROPRIETARY AND CONFIDENTIAL TO LOWE'S COMPANIES, INC., AND CANNOT BE COPIED OR OTHERWISE REPRODUCED OR USED WITHOUT THE EXPRESS WRITTEN PERMISSION OF LOWE'S.

FONT USAGE:
ARIAL REGULAR & BOLD SHOULD BE USED FOR ALL TEXT

INSERT PRODUCT DESCRIPTOR (AS WRITTEN ON THE PACKAGING).

ITEM NUMBERS AND MODEL NUMBERS ARE ARIAL REGULAR, 10 PT., ALIGN RIGHT. **ITEM NUMBERS MUST HAVE 7 DIGITS**. IF NECESSARY, ADD ZEROS TO THE BEGINNING OF THE NUMBER UNTIL THERE ARE 7 DIGITS.

1. VENDOR IS TO REPLACE ® WITH ™ IN LOGO WHEN APPLICABLE. THE SAME (BLACK & WHITE) LOGO APPROVED FOR PACKAGING IS TO BE USED IN THIS INSTRUCTION MANUAL.
2. TEXT IS 9 PT. ARIAL REGULAR, LIVE SPACING (LEADING) IS 11 PT. ALIGN LEFT. NOTE TO VENDOR: PLACE THE ACTUAL BRAND NAME AS SEEN ON THE LOGO.
3. INSERT REGISTERED TRADEMARK NOTICE (BELOW LOGO) IF PRODUCT IS A ® LOGO MARK ONLY.

INSTRUCTION TEXT MUST BE ON THE LEFT OF THE STEP AND STEP DIAGRAMS ON THE RIGHT. INSTRUCTIONS MUST BE WRITTEN USING CLEAR, CONCISE STATEMENTS IN ACTIVE VOICE.
→ **EXAMPLE**: ATTACH LEG (A) TO FRAME (F) WITH M6 x 12 BOLTS (DD).

DIAGRAMS MUST BE NUMBERED (I.E.: 1, 2, 3, ETC.). THE ASSEMBLY INSTRUCTION ILLUSTRATED STEP MUST REFERENCE THE CORRESPONDING TEXT, AND THE LETTER USED TO REFERENCE THE PARTS IN THE PACKAGE CONTENTS LIST MUST COME IN THE TEXT RIGHT AFTER THE PART NAME.

INSERT LINE ART DIAGRAM TO ILLUSTRATE EACH ASSEMBLY STEP. EACH DIAGRAM MUST BE ENCLOSED WITH A 1 PT. RULED BOX, AND MAY HAVE ONLY ONE ACCOMPANYING STEP.

Place logo in area shown. Scale logo to fit; if logo is horizontal, scale to fit width of box. If logo is vertical, scale logo to fit height of box.

Product descriptor is 20 pt. Arial Bold, line spacing (leading) is 24 pt. Align left.

Text is 10 pt. Arial Regular, line space (leading) is 12 pt. Align left.

Section header is 10 pt. Arial Bold, all caps. Rule is 2 pt. Section headers (including rule) can be moved up or down as needed.

Text corresponding to the step on right aligns with top of step box.

Text is 10 pt. Arial Regular, line space (leading) is 12 pt. Align left. Use pre-set tab for indent.

Assembly box rule should be 1 pt. Boxes are a minimum of 1-3/8 in. x 1-3/8 in.

Number is 12 pt. Arial Bold, centered in black box.

Raster line art (jpegs, tifs, etc.) should be high-resolution (300 dpi or greater) at full size. Vector line art (eps, ai, etc.) line weight no lower than 0.5 points or greater at full size.

Guides (lines) indicate 1/4 in. margin on the top, bottom, and outside edge, and 1/6 in. margin on inside edge. Keep all text and illustrations within the guides (lines).

Bulleted text is 10 pt. Arial Regular, line spacing (leading) is 16 pt. Align left.

Do not move the position of the top page header.

Section header is 10 pt. Arial Bold, all caps. Rule is 2 pt.

ITEM #0000000
MODEL #0000000

PRODUCT DESCRIPTOR

Call customer service at 1-XXX-XXX-XXXX, X a.m. - X p.m., PST, Monday-Friday.

OPERATING INSTRUCTIONS

1. Insert instruction text here. Insert instruction text here. Insert instruction text here. Insert instruction text here. Insert instruction text here. Insert instruction text here. Insert instruction text here.



2. Insert instruction text here. Insert instruction text here. Insert instruction text here. Insert instruction text here. Insert instruction text here. Insert instruction text here. Insert instruction text here.



3. Insert instruction text here. Insert instruction text here. Insert instruction text here. Insert instruction text here. Insert instruction text here. Insert instruction text here. Insert instruction text here.

4. Insert instruction text here. Insert instruction text here. Insert instruction text here. Insert instruction text here. Insert instruction text here. Insert instruction text here. Insert instruction text here.



Insert instruction text here. Insert instruction text here. Insert instruction text here. Insert instruction text here. Insert instruction text here. Insert instruction text here. Insert instruction text here.



HELPFUL TIPS

- Helpful tips go here as bulleted copy.
- Helpful tips go here as bulleted copy.
- Helpful tips go here as bulleted copy.
- Helpful tips go here as bulleted copy.
- Helpful tips go here as bulleted copy.

SAFETY INFORMATION

Insert safety information here. Safety information. Safety information. Safety information. Safety information. Safety information.

Can include all ratings if applicable.
125VAC / 60Hz
15A / 1875W Resistive (General Purpose)
10A / 1250W Tungsten (Incandescent)
1/2 HP (Horsepower Motor)

FPO

⚠ WARNING

- Place warning text here
- Place warning text here
- Place warning text here
- Place warning text here

CAUTION

- Place caution text here
- Place caution text here
- Place caution text here
- Place caution text here

CARE AND MAINTENANCE

Any applicable care and maintenance information goes here.

TROUBLESHOOTING

PROBLEM	POSSIBLE CAUSE	CORRECTIVE ACTION
Insert problem text here.	Insert possible cause text here.	Insert corrective action text here.
Insert problem text here.	Insert possible cause text here.	Insert corrective action text here.
Insert problem text here.	Insert possible cause text here.	Insert corrective action text here.
Insert problem text here.	Insert possible cause text here.	Insert corrective action text here.

WARRANTY

Insert warranty copy here.....
warranty warranty warranty warranty warranty
warranty warranty warranty warranty warranty
warranty warranty warranty warranty warranty
warranty warranty warranty warranty warranty
warranty warranty warranty warranty warranty
warranty warranty warranty warranty warranty
warranty warranty warranty warranty warranty
warranty warranty warranty warranty warranty
warranty warranty warranty warranty warranty
warranty warranty warranty warranty warranty
warranty warranty warranty warranty warranty
warranty warranty warranty warranty warranty
warranty warranty warranty warranty warranty
warranty warranty warranty warranty warranty
warranty warranty warranty warranty warranty
warranty warranty warranty warranty warranty
warranty warranty warranty warranty warranty
warranty warranty warranty warranty warranty

Text is 10 pt. Arial Bold, line spacing (leading) is 10 pt. Align left. Tables are formatted with pre-set tabs.

Some problems will have multiple causes and corrective actions; add or delete rows as necessary.

Text is 10 pt. Arial Regular, line spacing (leading) is 10 pt. Align left. Tables are formatted with pre-set tabs.

Warranty text is 10 pt. Arial Bold, line spacing (leading) is 12 pt. Align left.

Warranty text is 10 pt. Arial Regular, line spacing (leading) is 12 pt. Align left.

ENGLISH ON ONE SIDE LATIN AMERICAN SPANISH ON THE OTHER

INSERT WARNING AND CAUTION TEXT, INCLUDE WARNINGS AND/OR CAUTIONS SPECIFIC TO THE PRODUCT. INCLUDE ANY WARNINGS/CAUTIONS THAT ARE REQUIRED BY LAW.

"DANGER" SHOULD ALERT READERS TO THE THREAT OF DEATH.

"WARNING" SHOULD ALERT READERS TO THE THREAT OF PERSONAL INJURY.

"CAUTION" SHOULD ALERT READERS TO THE POSSIBILITY OF PRODUCT OR PROPERTY DAMAGE.

ACCORDING TO THE MAGNUSON-MOSS WARRANTY ACT, WARRANTIES MUST USE SIMPLE LANGUAGE AND STRUCTURE, A PERSONAL WRITING STYLE, AND CLEAR, UNDERSTANDABLE TERMS. WARRANTY MUST INCLUDE THE FOLLOWING INFORMATION:
1. THE CUSTOMER SERVICE NUMBER.
2. IS IT A FULL OR A LIMITED WARRANTY?
3. WHAT DOES THE WARRANTY COVER AND NOT COVER?
4. WHAT IS THE LENGTH OF COVERAGE?
5. WHAT WILL WARRANTOR DO TO CORRECT PROBLEM(S)?
6. HOW CAN THE CUSTOMER GET WARRANTY SERVICE?
7. HOW WILL STATE LAW AFFECT CUSTOMER'S RIGHTS?

XXXXX

INSERT PLACEHOLDER COPY FOR CODE GIVEN BY REVIEWERS

Printed in XXXXX

INSERT COUNTRY WHERE MANUAL IS BEING PRINTED. ALIGN RIGHT

3-Page Z-Fold
(All English One Side - Spanish the Other Side)

Updated 03/10/17